

Technical Datasheet



SN1-24

Plugin Power Supply

Plugin Power Supply – SN1-24

Description

The power supply SN1-24 is designed to operate units requiring a 24 V DC supply with 6 W maximum power from the mains. The SN1-24 is for indoor use only.

Operation

Note:

Ever disconnect the SN1-24 from the mains before you make changes on the 24 V installation!

Connect the red cable to the terminal "+24 V" (with KEM FA*, TCE * and KCE * terminal 50) and the white cable to terminal "-24 V" or "24 V GND" (with KEM FA*, TCE * and KCE * terminal 51). For the correct procedure refer to the unit's manual.

Put the SN1-24 into the wall socket.

Technical Data

Protection Class	II
Primary	
Supply Voltage	100 - 240 V AC ± 10 %
Frequency	47 - 63 Hz
Connector	Euro connector
Secondary	
Voltage	24 V ± 3 %
Current	250 mA max.
Power	6 W max., short circuit proof

Ordering Information

IPS 7-9	Wall plugin power supply 24 V/6 W
---------	-----------------------------------

KEM Headquarters

Liebigstraße 5
85757 Karlsfeld
Germany

T. +49 8131 59391-0
F. +49 8131 92604
info@kem-kueppers.com

KEM Manufacturing Center

Wetzeller Straße 22
93444 Bad Kötzing
Germany

T. +49 9941 9423-0
F. +49 9941 9423-23
production@kem-kueppers.com

KEM Sales

Liebigstraße 5
85757 Karlsfeld
Germany

T. +49 8131 59391-100
F. +49 8131 92604
sales@kem-kueppers.com

KEM Service & Repairs

Wetzeller Straße 22
93444 Bad Kötzing
Germany

T. +49 9941 9423-37
F. +49 9941 9423-24
service@kem-kueppers.com

*More distributors & partners can be found at:
www.kem-kueppers.com*